

Vibrator electric Convertizor de inalta frecventa



Echipamente
fabricate in
Italia

Seria NW

Cadru de metal pentru protectie
Disjunctor termic
Gama de pana la 5 kVA



Convertizor	NW 0582	NW 0586	NW 0588
Motor electric	1.0 kW - 400V	2.0 kW - 400V	1.0 kW - 230V
Disjunctor termic	Da	Da	Da
Amperaj	14 A	28 A	14 A
Lance	1 Ø 38 - 50 mm	2 Ø 38 - 50 mm 1 Ø 60 mm	1 Ø 38 - 50 mm



Convertizor	NW 0590	NW 0600	NW 0620	NW 0500
Motor electric	1.5 kW - 230V	3.0 kW - 400V	2.5 kW - 230V	5.0 kW - 230V
Disjunctor termic	Da	Da	Da	Da
Amperaj	21 A	42 A	35 A	70 A
Lance	2 Ø 38 - 50 mm 1 Ø 60 mm	3 Ø 38 - 50 mm 2 Ø 60 - 70 mm	2 Ø 38 - 50 mm 2 Ø 60 - 70 mm	4 Ø 38 - 50 mm 4 Ø 60 - 70 mm

Lance	VT 470	VT 472	VT 478	VT 474	VT 480
Diametru	Ø 38 mm	Ø 50 mm	Ø 60 mm	Ø 70 mm	Ø 80 mm
Aplitudine	1.3 mm	1.5 mm	1.8 mm	2 mm	3 mm
Capacitate compactare	6 - 8 m ³ /h	9 - 12 m ³ /h	18 - 23 m ³ /h	20 - 25 m ³ /h	27 - 30 m ³ /h
Lungime lance	320 mm	330 mm	410 mm	410 mm	475 mm
Lungime furtun	5 m				
Nr. vibratii	12.000 rpm				
Lungime cablu	10 m				
Frecventa	200 Hz.				

Distribuitor local