

Jet 45 - 70

Echipare standard

Pompa Robin / Motor Subaru-Robin Japonia
 Racire cu aer - filtru inclus
 Senzor lipsa ulei - opreste functionarea
 Cadru ranforsat din otel grosime 3 mm

Accesorii incluse

1 x sita de aspiratie
 2 x racorduri
 3 x coliere
 1 x cheie bujii

Echipare optionala

Kit roti
 Rezervor marit 15 l
 Kit intretinere (filtre + ulei)



450 OHV



75/80 EX



70 EX - versiune antiincendiu include kit roti si furtun



70 D - versiune cu roti si carucior

Benzina sau Diesel

| Motopompe Seria JET | | 45 | 70 | 75 | 80 | 70 D |
|-------------------------------------|-------|-----------------------|--------------|--------------|--------------|--------------|
| | | OHV | EX | EX | EX | |
| | | PTV110 | PTX201 H | SER-40 | SER-50 | JET60 DC |
| Diam. aspiratie | mm | 25 | 50 | 50 | 65 | 40 |
| Diam. refulare | mm | 25 | 50 | 40 | 50 | 25/40 |
| Debit maxim | l/min | 125 | 400 | 400 | 600 | 400 |
| | mc/h | 7,5 | 24 | 24 | 36 | 24 |
| Presiune de lucru | Bar | 4,2 | 5 | 6 | 7 | 5 |
| Adancime maxima de aspiratie | m | 8 | | | | |
| Inaltime maxima de refulare | m | 42 | 50 | 60 | 70 | 50 |
| Granulometrie absorbita | mm | 5,5 | 5,5 | 2,5 | 2,5 | 5,5 |
| Tip Motor Subaru | | EH03 | EX17 | EX17 | EX27 | DY23 |
| Alimentare motor | | Benzina fara plumb 95 | | | | Diesel |
| Autonomie medie | Ore | 2,3 | 2,3 | 3,3 | 2,3 | 4 |
| Capacitate rezervor standard / XL15 | Litri | 0,65 | 3,6 | 3,6 | 6,1 | 3,2 |
| Greutate totala utilaj | kg | 7,5 | 28 | 38 | 44 | 52 |
| Dimensiuni utilaj L/I/H | mm | 360/220 /345 | 539/368 /456 | 520/380 /420 | 520/470 /530 | 750/460 /525 |

Distribuitor local