

# Motopompa de spalat cu presiune



Echipament  
fabricat in  
Franta

## HPSTAR 200-15

Racord rotativ +

Cadru rezistent cu  
diametru de Ø 32 mm +



+ Roti pneumatice

Spalare cu presiune	HPSTAR 200-15
Presiune max.	200 bar
Debit	15 l/min. - 900 l/h
Turatie motor	3400 rpm
Tip pompa	Axial
Model pompa	Annovi Riverberi
Protectie temperatura	Termo valva
Motor	EX 27 DUL SH
Tip motor	OHC 4 timpi
Aspirare aer	Turbo
Putere max.	9.0 cp - 4000 rpm
Cilindri motor	265 cm <sup>3</sup>
Combustibil	Benzina
Capacitate rezervor	6.1 l
Autonomie	3h
Pornire motor	la sfoara
Senzor lipsa ulei	Da
Greutate	56 kg
Dimensiuni L/l/h (mm)	700 x 700 x 1060

### Echipare standard

Lance 1.1 m cu presiune ajustabila  
Duza din ceramica ce asigura o viata ultra-indelungata  
Furtun de presiune, 10 m lungime  
Manometru presiune  
Valva eliberare presiune  
Kit aplicare detergent inclus  
Protectie termica motor  
Sasiu sudat mecanic cu tubulatura Ø30 mm  
Protectie metal vopsita cu vopsea epoxy  
Maner cadru detasabil pentru a o transporta mai usor  
Roti pneumatice rezistente



[www.italiastar.ro](http://www.italiastar.ro)



Italia Star Com Due S.R.L.  
Autostrada București - Pitești km. 13.2  
Loc. Chiajna - Ilfov  
Tel: 021.433.03.27  
Fax: 021.433.03.26  
[info@italiastar.ro](mailto:info@italiastar.ro) [www.italiastar.ro](http://www.italiastar.ro)

