

COMBIPlus

POWERED by
HONDA

Made in Italy



G6500YEO

PANOU COMANDA

- 1 x priza Schuko 16A 230V
- 1 x priza CEE 16A 400V
- Intrerupator termic
- Intrerupator de circuit
- Afisaj orar, tensiune, voltmetru
- Intrerupator pornire/oprire
- Protectie la nivel scazut ulei



G11100KEO

PANOU COMANDA

- 1 x priza Schuko 16A 230V
- 1 x priza CEE 16A 400V
- Intrerupator termic
- Intrerupator de circuit
- Buton oprire de urgenta
- Afisaj orar, tensiune, voltmetru
- Intrerupator pornire/oprire
- Protectie la nivel scazut ulei



G15000HEO

PANOU COMANDA

- 1 x priza CEE 16A 230V
- 1 x priza CEE 32A 400V
- Intrerupator termic
- Intrerupator de circuit
- Buton oprire de urgenta
- Afisaj orar, tensiune, voltmetru
- Intrerupator pornire/oprire
- Protectie la nivel scazut ulei

Date tehnice

Model	G6500YEO	G11100KEO	G15000HEO
Putere LPT/PRP kW	5,5 / 4,5	9,8 / 8,8	11,9 / 10,8
Putere LPT/PRP kVA	6,9 / 5,6	12,3 / 11,0	14,9 / 11,9
Voltaj	230/400 V	230/400 V	230/400 V
Frecventa	50 Hz	50 Hz	50 Hz
Factor de putere	0,8	0,8	0,8
Regulator de tensiune	AVR	AVR	AVR
Amperaj LPT/PRP	10 / 8 A	18 / 16 A	21 / 20 A
Factor de protectie	IP 23	IP 23	IP 23
Tip motor	Cilindru dublu, 4 timpi	Cilindru dublu, 4 timpi	Cilindru dublu, 4 timpi
Model motor	YANMAR L100	KOHLER KD425/2	HONDA GX690 Stage V
Capacitate cilindrica	435 cc	851 cc	688 cc
Putere motor	10 CP	15,6 CP	25 CP
Turatie motor	3000 RPM	3000 RPM	3000 RPM
Racire	Aer	Aer	Aer
Carburant	Diesel	Diesel	Benzina
Capacitate rezervor	19 L	19 L	19 L
Autonomie	15 ore	8 ore	3,4 ore
Demaraj	Electric (baterie inclusa)	Electric (baterie inclusa)	Electric (baterie inclusa)
Greutate	124 kg	173 kg	166 kg
Dimensiuni L x l x h (mm)	810 x 550 x 680	870 x 620 x 690	870 x 620 x 690



www.italiastar.ro



Italia Star Com Due S.R.L.
Autostrada București - Pitești km. 13.2
Loc. Chiajna - Ilfov
Tel: 021.433.03.27
Fax: 021.433.03.26
info@italiastar.ro www.italiastar.ro