

Generator de curent stationar cu automatizare la pornire



| Generator | SCDE 19YSM |
|------------------------------|---------------------|
| Putere max. generator | 19 kVA / 15 kW |
| Putere generator continua | 17 kVA / 13.60 kW |
| Voltaj | 230 V |
| Frecventa | 50 Hz |
| Factor de putere | 0.8 |
| Amperaj | 24.5 A |
| Panou ATS | Inclus in standard |
| Motor | IND485D |
| Putere motor | 25 cp |
| Turatie motor | 1.500 rpm |
| Nr. cilindri motor | 4 vertical in linie |
| Aspirare aer | Normala |
| Preincalzire motor | Inclus in standard |
| Racire motor | Lichid racire |
| Capacitate lichid racire | 5,4 l |
| Carburant | Motorina |
| Consum combustibil | ≤ 235 g / kW / h |
| Autonomie la 70% putere | 26 ore |
| Capacitate rezervor | 80 l |
| Tip ulei | 15W40 / 15W50 |
| Capacitate rez. ulei | 4 l |
| Consum maxim de ulei | 0,25 % |
| Numar poli | 4 |
| Regulator de tensiune | AVR |
| Precizia tensiunii de iesire | ± 1% |
| Tip alternator | Senci S164G14C5 |
| Greutate neta | 650 kg |
| Dimensiuni LxIxh (mm) | 1.950 x 900 x 1.050 |

Model: SCDE 19YSM



Dotare standard panou cu automatizare DC42DMK3, display LCD cu afisare voltaj, frecventa, temperatura apa, presiune ulei, temperatura ulei.

Protectie generator IP23
Temperatura de lucru -15° + 70°C
Temperatura depozitare -30°C +80°C

*Acest model de generator nu poate fi transportat cu rezervorul incarcat peste 10% din capacitatea maxima.



www.italiastar.ro



Italia Star Com Due S.R.L.
Autostrada București - Pitești km. 13.2
Loc. Chiajna - Ilfov
Tel: 021.433.03.27
Fax: 021.433.03.26
info@italiastar.ro www.italiastar.ro

